lokum®

AT | LOKUM AMPLATZ TYPE GUIDE WIRE

combining positioning and extra support in one design



andratec®
ADVANCED INTERVENTIONAL TECHNOLOGIES

lokum® AT | LOKUM AMPLATZ TYPE GUIDE WIRE

- Design characteristics for positioning and extra support in one.
- High performance PTFE coated shaft providing low surface friction and enhanced trackability.
- Intended use during interventional peripheral and interventional biliary drainage procedures.
- Providing enhanced support during catheter and/or delivery system exchange.



Technical Information

Guide Wire Material	Extra Tempered Stainless Steel
Coating	High performance PTFE
Diameter	0.035" (0.89 mm)
Distal Tip	Straight / 3 mm J-Tip / 6 mm J-Tip
Tip Configuration	5 cm Flexible Tip
Shaft Length	180 cm / 260 cm / 360 cm

Order Codes

A choice of various diameters and lengths.

	3 mm	6 mm	∅	⊢ ⊣	
LOAM-180-ST	LOAM-180-3T	LOAM-180-6T	0.035" (0.89 mm)	180 cm	5 cm
LOAM-260-ST	LOAM-260-3T	LOAM-260-6T	0.035" (0.89 mm)	260 cm	5 cm
LOAM-360-ST	LOAM-360-3T	LOAM-360-6T	0.035" (0.89 mm)	360 cm	5 cm

andratec® ADVANCED INTERVENTIONAL TECHNOLOGIES

andra**tec** gmbh
Simmerner Straße. 70, 56075 Koblenz, Germany

Office & Warehouse
Im Deutschen Kaiser,
Kastorstraße 3, 56068 Koblenz, Germany
+49(0) 261 100 49 653
+49(0) 261 100 49 654
info@andratec.com

www.andratec.com

alliance partner

CE 0197

2026/05/01/P014/Rev 2E/Brochure

∅ GW Diameter (" / inch) ⊢ ⊣ GW Lenght (cm) Straight Tip (mm) J-Tip (mm) Flexible tip length