lokum®

LQ | LOKUM L-QUEST GUIDE WIRE

balanced combination of extra strong support, high pushability and variable tip lengths



andratec®
ADVANCED INTERVENTIONAL TECHNOLOGIES

lokum®
LQ | LOKUM L-QUEST GUIDE WIRE

- Especially designed for extra strong support high pushability and catheter / delivery system exchange.
- High performance PTFE coating providing low surface friction and enhanced trackability.
- Intended to use in complex diagnostic and interventional procedures.
- 3 tips flexibilities to ensure secure and safe positioning: 5 cm, 10 cm and 15 cm.



Technical Information

Lokum L-Quest Guide Wire

Guide Wire Material	Extra Tempered Stainless Steel
Coating	High performance PTFE
Diameter	0.035" (0.89 mm)
Distal Tip	Straight / 3 mm J-Tip / 6 mm J-Tip
Tip Configuration	5 cm / 10 cm / 15 cm Flexible Tip
Shaft Length	180 cm / 260 cm

Lokum L-Quest **Mini** Guide Wire

Guide Wire Material	Extra Tempered Stainless Steel
Coating	High Performance PTFE
Diameter	0.025" (0.635 mm)
Distal Tip	Straight / 3 mm J-Tip / 6 mm J-Tip
Tip Configuration	5 cm / 10 cm / 15 cm Flexible Tip
Shaft Length	180 cm / 260 cm

Order Codes

Lokum L-Quest Guide **0.035"**

	3 mm	6 mm	∅	⟷	≈
LOLU-05-180-ST	LOLU-05-180-3T	LOLU-05-180-6T	0.035" (0.89 mm)	180 cm	5 cm
LOLU-10-180-ST	LOLU-10-180-3T	LOLU-10-180-6T	0.035" (0.89 mm)	180 cm	10 cm
LOLU-15-180-ST	LOLU-15-180-3T	LOLU-15-180-6T	0.035" (0.89 mm)	180 cm	15 cm
LOLU-05-260-ST	LOLU-05-260-3T	LOLU-05-260-6T	0.035" (0.89 mm)	260 cm	5 cm
LOLU-10-260-ST	LOLU-10-260-3T	LOLU-10-260-6T	0.035" (0.89 mm)	260 cm	10 cm
LOLU-15-260-ST	LOLU-15-260-3T	LOLU-15-260-6T	0.035" (0.89 mm)	260 cm	15 cm

Lokum L-Quest **Mini** Guide **0.025"**

	3 mm	6 mm	∅	⟷	≈
LUMI-05-180-ST	LUMI-05-180-3T	LUMI-05-180-6T	0.025" (0.635 mm)	180 cm	5 cm
LUMI-10-180-ST	LUMI-10-180-3T	LUMI-10-180-6T	0.025" (0.635 mm)	180 cm	10 cm
LUMI-15-180-ST	LUMI-15-180-3T	LUMI-15-180-6T	0.025" (0.635 mm)	180 cm	15 cm
LUMI-05-260-ST	LUMI-05-260-3T	LUMI-05-260-6T	0.025" (0.635 mm)	260 cm	5 cm
LUMI-10-260-ST	LUMI-10-260-3T	LUMI-10-260-6T	0.025" (0.635 mm)	260 cm	10 cm
LUMI-15-260-ST	LUMI-15-260-3T	LUMI-15-260-6T	0.025" (0.635 mm)	260 cm	15 cm

andratec®
ADVANCED INTERVENTIONAL TECHNOLOGIES

andra**tec** gmbh
Simmerner Straße. 70, 56075 Koblenz, Germany

Office & Warehouse
Im Deutschen Kaiser,
Kastorstraße 3, 56068 Koblenz, Germany
+49(0) 261 100 49 653
+49(0) 261 100 49 654
info@andratec.com

www.andratec.com

alliance partner

CE 0197

∅ GW Diameter ("/inch) ⟷ GW Lenght (cm) Straight Tip (mm) J-Tip (mm) Flexible tip length

2026/05/01/P015/Rev 2E/Brochure